


NIGERIAN ELECTRICITY MANAGEMENT SERVICES AGENCY (NEMSA)





NIGERIAN ELECTRICITY MANAGEMENT SERVICES AGENCY



GUIDELINES FOR THE INSPECTION OF SOLAR MINI-GRIDS IN NIGERIA

Date of Publication August, 2020

Published by:

Nigerian Electricity Management Services Agency

Contact:

Nigerian Electricity Management Service Agency 4 Dar-Es-Salaam Street, Wuse, Abuja, FCT, Nigeria

Email: info@nemsa.gov.ng

ISBN: 978-978-983-567-6

Date of Publication:

August 2020

This publication was produced with the financial assistance of the European Union and the German Government through the Nigerian Energy Support Programme (NESP). The views expressed herein can in no way be taken to reflect the official opinions of the European Union and the German Government.

Nigerian Energy Support Programme (NESP)

No 2 Dr. Clement Isong Street, Asokoro

Abuja/Nigeria

Email: nesp@giz.de

NESP is co-funded by the European Union & the German Government







Preface

The Nigerian Electricity Management Services Agency (NEMSA) was established by the NEMSA Act, 2015, to carry out the functions of Enforcement of Technical Standards and Regulations, Technical Inspection, Testing and Certification of all categories of Electrical Installations, Electricity Meters and Instruments etc. to ensure the efficient production and delivery of safe, reliable and sustainable electricity power supply and guarantee safety of lives and property in the Nigerian Electricity Supply Industry (NESI), other allied industries and premises.

Solar mini-grids are increasingly recognized as a key solution to increase electricity access in a timely and sustainable manner. The Guidelines for Inspection of Solar Mini-grids is a publication of NEMSA developed with technical support from the Nigerian Energy Support Programme (NESP) co-funded by the European Union (EU) and the German Government and implemented by Deutsche Gesellschaft für Internationale Zusammenarbeit (GIZ) in collaboration with the Federal Ministry of Power (FMP). The Guidelines outline the application, inspection and certification procedures/processes and documentation of Solar Mini-grids in Nigeria to achieve standardization and unification, and, ultimately, the safety of the system.

These Guidelines were developed and produced in line with National and International Law, Technical Standards, Regulations, Codes and Specifications and best electrical installations and construction practices. These include, but are not limited to: The NEMSA Act, 2015; The applicable International Electrotechnical Commission (IEC) standards; The Nigerian Electricity Health and Safety Code, 2014; The Nigerian Electricity Supply and Installation Standards (NESIS) Regulation, 2015; The Nigerian Electricity Smart Metering Regulations, 2015; The Grid Code, 2018; The Distribution Code, 2014; The Metering Code (V02), 2014; The Mini-Grid Regulations, 2016, The Electrical Installations Regulations S.I.5 and Electricity Supply Regulations S.I.6, 1996 etc.

The enforcement of Technical Standards and Technical Regulations aims to ensure a safe and reliable operation of the Solar Mini-grid System. This is achieved by ensuring that the System, including all its components, is correctly designed, specified, installed, inspected and certified to supply power to residential, commercial, industrial and institutional users in a safe manner in conformity with the applicable Technical Standards and Technical Regulations.

These Guidelines, therefore, fill a technical gap in the enforcement of Technical Standards and Technical Regulations in the Solar Mini-grid space.

Acknowledgements

The Nigerian Electricity Management Services Agency (NEMSA)would like to acknowledge the cooperation of all the key NESI stakeholders that took part in the development of these Guidelines for Inspection of Solar Mini-grids in Nigeria, particularly the Nigerian Energy Support Programme (NESP) co-funded by the European Union and the German Government and implemented by Deutsche Gesellschaft für Internationale Zusammenarbeit (GIZ) in collaboration with the Federal Ministry of Power.

Engr. Peter O. Ewesor

Chief Electrical Inspector of the Federation

Content

Acr	onyms	6
1	Definitions	7
	Scope	
3	Process	13
4	Inspection Certificate issuance	16
5	Sanction for non-compliance	17
6	Dispute settlement	17
7	Process Flow Diagram	18
8	Annex – Mini-grid Documentation and Inspection Forms	19

Acronyms

AC Alternating Current

BoS Balance of System

C Current

CEIF Chief Electrical Inspector of the Federation

DC Direct Current

FMP Federal Ministry of Power

GIZ Deutsche Gesellschaft für Internationale Zusammenarbeit

IEC International Electro-technical Commission

kV Kilo-Volt: 1,000 Volts

KW Kilo-Watts

KWH Kilo-Watt-Hour

kVA Kilo-Volt-Ampere

MD Minor Deviation

MD/CEO Managing Director/Chief Executive Officer

MPPT Maximum Power Point Tracking

MW Mega-Watts

NEMSA Nigerian Electricity Management Services Agency

NERC Nigerian Electricity Regulatory Commission

NESI Nigeria Electricity Supply Industry

NESIS Nigeria Electricity Supply and Installation Standards

NESP Nigerian Energy Support Programme

PV PhotoVoltaic

SLD Single Line Diagram

V Volt(s)

SON Standards Organisation of Nigeria

SR Safety Relevant

Definitions

Applicant

shall mean the Mini-grid Owner, also referred to as Owner in these Guidelines, who may authorise a third-party that is fully familiar with the Mini-Grid, to apply and procure the Inspection Certificate on its behalf, provided that he is a NEMSA certified Renewable Energy contractor for Electricity Generation.

Back-up Generation

shall mean any firm Generation such as diesel- or biomasspowered-generator that can operate within seconds of the nonavailability of the Solar Photovoltaic (PV) Generation.

Balance of System (BoS)

shall mean and encompass all components of a PV system other than the PV panels; including wiring, switches, a mounting system, one or many solar inverters, a battery bank or many battery banks, related electronic battery converters and battery chargers.

Customer

shall mean and include a client of the Owner buying electricity from the Mini-Grid under a domestic, commercial, productive and/or administrative service contract, and may be a natural person or any other legal entity.

Commissioning

shall mean the period when all installations for the Mini-grid have been completed and technically inspected, tested and certified by NEMSA before the mini-grid can start Operations.

Commissioning Report

shall comprise all forms, duly completed, and accompanying information as required by the present Guidelines as well as all other applicable Laws, Regulations and Standards.

Distribution Network

shall mean electric power lines with connections for low voltage (230/400V) and optionally medium voltage (up to 33kV), transformers and other switchgear to distribute electric power produced by the Generation as well as Meters in the Mini-Grid to the Customers.

Electrical Installation

means the construction or installation of electrical wiring and the permanent attachment or installation of electrical products in or on any structure.

Electrical Safety

means any safety precautions (organisational measures and technical) taken against electricity (electric current, electric arc, electromagnetic field and static electricity) to prevent harmful and dangerous effects on anyone.

Guidelines

Shall mean these Guidelines for the Technical Inspection of

Solar Mini-Grids in Nigeria, as issued by NEMSA.

Generation

shall mean the Solar PV Generation in combination with any Other Generation and Back-up Generation, as well as the land (including the Powerhouse and the Fencing) where the

Generation is installed.

Inspection

shall mean the physical inspection and testing of the Owner's Solar Hybrid Mini-grid Electrical Installation by NEMSA inspectors as per the procedure described in these Guidelines.

Inspection Certificate

shall mean the Certificate issued by NEMSA to any Owner of a Solar Hybrid Mini-grid having successfully undergone the process of Inspection by NEMSA Inspectors, as defined in these Guidelines, and being valid for a period of 5 years, unless the Electrical Installation requires Significant Modifications prior to this period, in which case the Owner shall

apply for Re-inspection.

Inspection Fee

shall be the fee stipulated for the purpose of inspection of Mini-Grid as published by NEMSA on www.nemsa.gov.ng.

Law

shall mean NEMSA Act, 2015, and any Act as approved by the Federal or State legislatures in Nigeria.

Meter

shall have the meaning given to it in the Nigerian Electricity Regulatory Commission (NERC), Metering Code, V02, NEMSA Act, 2015.

Mini-grid

shall mean "any electricity supply system with its own power Generation capacity of up to 1 MW, supplying electricity to more than one customer and which can operate in isolation from or be connected to a Distribution Licensee's network", in accordance with NERC's, Mini-grid Regulations, 2016.

Mini-grid Documentation and Inspection Forms

shall mean the standardized document to be filled by the Applicant to apply for Inspection annexed to these Guidelines, which shall be subject to changes by NEMSA and for which the latest version can be downloaded from www.nemsa.gov.ng or picked up in any of the NEMSA Inspectorate Field Offices (https://nemsa.gov.ng/field-inspectorate-offices/).

NEMSA Certified Contractor

shall mean any Renewable Energy Contractor duly certified by NEMSA to carry out Renewable Energy projects such as solar, biomass, wind etc.

NEMSA Inspector

shall mean an inspecting Engineer holding such office under NEMSA to carry out the functions of inspection, testing and certification of all electrical installation as stated in this Guidelines.

NEMSA Inspectorate Field Office

shall mean any of NEMSA's field offices located in any of the geo-political zones in Nigeria or as may be established from time to time and published on NEMSA's website.

Operating Procedures

shall mean written internal instructions of the Mini-Grid Owner to its technical and administrative staff on how to operate the Mini-grid (including to connect and service Customers), which shall comprise of procedures on personal safety, fire prevention, environmental protection and emergency shutdown, general conditions and procedures of public relevance, prices and service conditions for the Customers, a copy of the latest edition of the Inspection Certificate, where applicable, contact telephone numbers and contact details for electronic communication, and that shall be publicly displayed and accessible to Customers at the Mini-grid Powerhouse.

Operations

shall be the period starting when the Mini-grid commences its commercial activities by providing electricity services to Customers in exchange for a fee.

Other Generation

shall mean any Generation that is not Solar PV or Back-up Generation such as wind or biomass that can produce electricity in combination with the above-referred types of Generation in the Mini-grid.

Owner

shall mean any company registered and owning Mini-grids in Nigeria, as per NERC, Mini-Grid Regulations, 2016.

Provisional Inspection Certificate shall mean an Inspection Certificate giving permission to start Servicing Customers with electricity for a period limited to 30 days before the Owner obtains the Inspection Certificate.

Regulation

shall mean any applicable piece of Regulation, as approved by the NERC or any other statutory regulatory body in Nigeria.

Re-inspection

shall mean Inspection after correcting the defects observed during Inspection or upon expiry of the Inspection Certificate for reasons of renewal of the Inspection Certificate or upon Significant Modifications carried out by the Mini-Grid Owner, and shall follow the same procedure as Inspections.

Servicing

shall mean the sale of electricity by a Mini-Grid Owner to Customers.

Significant Modifications

shall mean any Modification requiring a Re-inspection

- 1. including the following or comparable Modifications:
 - a. Relocation of the Generation to a different location in the distribution network;
 - b. Change of the overall System Controller or Balance of System (BoS); and
 - c. any other modification that requires an approval under the Applicant's Mini-Grid Permit
- 2. excluding any of the following or comparable Modifications:
 - Extension of any existing power line by no more than 3 utility poles to connect new Customers;
 - Extension of the existing Solar PV Generation capacity, up to maximum of 30%, that does not require replacement of equipment and supply cables;
 - Replacement of the existing Back-up Generation of same or maximum 30% larger rated power;
 - Replacement of the existing Storage and extension by added parallel battery banks or parallel Storage systems;

All above exempted modifications are subject to notification to NEMSA for record purposes.

Solar Hybrid Mini-grid

shall mean any Mini-grid that combines Solar PV Generation, Other Generation, Back-up Generation and a Distribution Network, as per NERC, Mini-grid Regulations, 2016, and the Glossary of the present Guidelines.

Solar PV Generation

shall mean the main Generation source of the Solar Hybrid Mini-grid and comprising the solar modules, the ground/roof mounted or building integrated support structure, the charge controller or grid-tie inverter and the required Balance of Systems (BoS), if not part of the System Controller.

Standard

shall mean any Standard as recommended by NERC, NEMSA and/or approved by SON or the International Electro-technical Commission (IEC).

Storage

shall mean secondary (rechargeable) batteries, including, but not necessarily limited to lead-acid batteries and lithium to store excess electricity produced by the Generation for later use, including power electronic converters or charge controllers and monitoring, if not part of the overall System Controller.

System Controller

shall mean the central element of the Generation to manage all types of Generation and Storage of the Mini-grid to ensure reliable supply of electricity to the Distribution Network of the Mini-Grid, and shall comprise of a simple charge controller for small systems (i.e. up to 10kW) and of dedicated off-grid inverters or a supervisory controller in combination with dedicated controllers and electronic power inverters for large systems (i.e. from 10kW), including all required BoS.

Technical Committee

shall mean committee put in place by NEMSA to review the complaints from Applicants, in line with Part 5 Section 14 (5) of the NEMSA Act, 2015.

Technical Documentation

shall mean data sheets, Single Line Diagrams (SLDs), detailed schematics, construction plans, internal test and Commissioning reports/protocols as well as Operating Procedures by the Mini-Grid Owners.

2 Scope

- The present Guidelines describe the process and standards to be followed by the Owner (Applicant) of a Solar Hybrid Mini-grid while applying for Inspection or Re-Inspection and by NEMSA while Inspecting or Re-Inspecting Solar Hybrid Mini-grids.
- The Inspection of Solar Hybrid Mini-grids by NEMSA shall be made in close consultation
 with the Applicant who shall endeavour to grant full collaboration to NEMSA; which, in turn,
 shall ensure a timely issuance of the Inspection Certificate in observance with the
 applicable Laws, Regulations and Standards.
- 3. The Guidelines shall be read and implemented together with other Laws, Regulations and Standards in the following order:
 - Laws of the Federal Republic of Nigeria, including but not limited to the NEMSA Act, 2015.
 - b. Regulations from NERC, including but not limited to:
 - i. The Nigerian Electricity Health and Safety Code, 2014.
 - ii. The Nigerian Electricity Supply and Installation Standards Regulation, 2015.
 - iii. The Grid Code, 2018

- iv. The Distribution Code, 2014
- v. The Metering Code (V02), 2014
- vi. Nigerian Electricity Smart Metering Regulations, 2015
- vii. The Mini-Grid Regulations, 2016
- viii. Electrical Installations Regulations S.I.5 and Electricity Supply Regulations S.I.6 of 1996; and
- ix. Other technical regulations, guidelines and codes issued by NERC or NEMSA from time to time.
- c. Guidelines as developed by NEMSA and other institutions and bodies in Nigeria, which are in line with extent laws and regulations, including but not limited to:
 - i. These Guidelines; and
 - The Nigerian Electrical Installations and Construction Guidelines Manual, Distribution Subsector, Volume 1, 2020.
- d. Standards of the International Electro-Technical Commission (IEC), especially for technologies that are not covered under any Nigerian Law, Regulation or Standard, including but not limited to:
 - i. IEC 62446-1:2016+A1:2018: PV systems Requirements for testing, documentation and maintenance - Part 1: Grid connected systems -Documentation, commissioning tests and inspection;
 - ii. IEC 60896-21:2004: Stationary lead-acid batterie Part 21: Valve regulated types Methods of test;
 - iii. IEC 62485-1:2015: Safety requirements for secondary batteries and battery installations Part 1: General safety information;
 - iv. IEC 62619:2017: Secondary cells and batteries containing alkaline or other non-acid electrolytes Safety requirements for secondary lithium cells and batteries, for use in industrial applications; and
 - v. IEC 62620:2014: Secondary cells and batteries containing alkaline or other non-acid electrolytes Secondary lithium cells and batteries for use in industrial applications.
- 4. In case of conflicts between the present Guidelines and other NEMSA Guidelines, these Guidelines shall take precedence over other NEMSA Guidelines where the said conflict is in relation to the Technical Inspection of Solar Mini-Grids as long as it is in line with the extant Regulation.
- 5. The Guidelines shall be subject to a review by NEMSA every five (5) years.

3 Process

3.1 Requirement for an Inspection Certificate

Pursuant to the provisions of these Guidelines, an Inspection Certificate shall be required in either of the following circumstances:

- Prior to Operations, the Owner of any Electrical Installation shall apply for Inspection by NEMSA and shall be entitled to an Inspection Certificate upon completion of Satisfactory Inspection.
- 2. Three (3) months before the expiry of the Inspection Certificate or immediately upon the completion of Significant Modifications, the Owner of an Electrical Installation shall apply for Re-inspection by NEMSA for the purpose of renewing the Inspection Certificate.

3.2 Application

- The Applicant shall apply for Inspection no later than one (1) month prior to Commissioning
 or with respect to Re-inspection, shall apply for Re-inspection after five (5) working days of
 the issuance of the Provisional Inspection Certificate by NEMSA or upon the completion of
 Significant Modifications.
- 2. Upon the completion of the construction phase of the Solar Hybrid Mini-Grid, the Applicant shall fill in the Sections of the Mini-grid Documentation and Inspection Forms that require the Applicant's action as per the table below and submit them along the Technical Documentation electronically or to the respective NEMSA Inspectorate Field Office to request for an Inspection.

Form	Title	Remarks
Α	General Form	To be filled in by the Applicant
В	PV Generator	Includes 'Applicant Section'
С	Battery storage	Includes 'Applicant Section'
D	System Controller	Includes 'Applicant Section'
Е	Earthing and Surge Protection System	Includes 'Applicant Section'
F	General Security	Includes 'Applicant Section'

- 3. NEMSA shall validate the Mini-grid Documentation and Inspection Forms and any accompanying Technical Documentation within a period of five (5) working days. Where the documentation is not valid or incomplete, NEMSA shall request for rectification, and the Applicant shall submit the rectified and/or complete documentation within a period of five (5) working days.
- Upon validation, NEMSA shall also issue a request for payment of Inspection Fee and propose a date for Inspection, and the Applicant shall pay the Inspection Fee within a period of 5 days.

Upon receipt of Inspection Fee, NEMSA shall communicate a suitable date for the inspection to the Applicant within five (5) working days, and the Applicant shall confirm the date NEMSA suggested before the inspection exercise.

3.3 Inspection

- 1. Once the proposed inspection date has been agreed, the designated NEMSA Inspector shall undertake an Inspection with the Applicant in accordance with these Guidelines.
- 2. The Mini-grid shall be fully operational at the time of the Inspection; however, no Customer shall have been connected or served yet.
- The Applicant shall have conducted internal tests and measurements to prove the electrical safety of the complete Electrical Installation before the Inspection and to make the reports available to the NEMSA Inspectors.
- The Technical Documentation should be submitted along with other documents for inspection to the NEMSA Inspector.
- During the Inspection, the NEMSA Inspector shall use the Agency's relevant test equipment for the measurements and/or to ask the applicant to repeat some test for NEMSA's observations/verifications.
- 6. The Inspection shall comprise of the following steps:
 - Guided walk-around conducted by the Applicant in the community starting with the Generation, administrative offices, main power lines, point of interconnection with other mini-grids – if available, potential main Customers, etc.
 - b. Inspection of the Distribution Network, which will include, but not be limited to:
 - i. Distribution grid pole installation;
 - ii. Distribution grid wiring; and
 - iii. Street lightning (where applicable).
 - iv. Metering installation (where applicable).
 - c. Inspection of the Generation (excluding the Storage), which will include but not limited to:
 - i. PV module quality;
 - ii. PV module array foundation;
 - iii. PV array mounting structure; and
 - iv. PV array combiner box and internal wiring.
 - d. Inspection of the Storage (including battery status and inverter performance).
 - e. Inspection of Powerhouse, which will include, but not be limited to:
 - i. Internal powerhouse wiring;
 - ii. Powerhouse foundation:
 - iii. Powerhouse general condition;

- iv. Powerhouse ventilation; and
- v. Powerhouse flooding prevention.
- f. Inspection of the Technical Documentation (incl. Operating Procedures).
- q. Measurements and validation of the Measurements:
 - The NEMSA Inspector shall repeat selected measurements already carried out by the contractor, if there is need for such, as part of the Inspection.
 - ii. Tests and measurements related to Electrical Safety shall be in accordance with the Nigerian Electricity Health and Safety Code issued by NERC and safety requirement of extant regulation, The Nigerian Electrical Installations and Construction Guidelines Manual, Distribution Subsector, Volume 1, 2020 issued by NEMSA and shall comprise, at least, of the following aspects: the earthing resistance; continuity of the equipotential bonding; and leakage current or insulation resistance.
- Inspection of Owner's comprehensive occupational safety programme, including a written safety policy and an accident investigation program.
- 7. The Mini-grid Documentation and Inspection Forms partly filled and submitted to NEMSA by the Applicant shall be used as the basis for the Inspection.
- 8. Completion of the sections of the Mini-grid Documentation and Inspection Forms to be filled by the NEMSA Inspector and explanation of the preliminary results of the Inspection to the Applicant on site.
- 9. In the sections of the Mini-grid Documentation and Inspection Forms marked "To be filled in by NEMSA", the NEMSA Inspector may add a comment or observation from verification of the data sheets, verification of the measurements and test reports of the Applicant, own measurements, or observations in the field.
- 10. The Inspector shall include comments, if any, as follows:
 - a. MD: Minor Deviation to be rectified without impeding the safety.
 - b. SR: Safety Relevant deviation to be rectified.
- 11. The NEMSA Inspector shall mark the fields using the symbols and as illustrated in the exemplary table below.
 - a. X To indicate that there is an issue in this specific combination of observation and category (MD or SR)
 - b. --- To indicate that there is no issue in this specific combination of observation and category (MD or SR)

To be filled in by NEMS	SA	
Comment	MD	SR
Observation 1		X

To be filled in by NEMSA		
Comment	MD	SR
Observation 2	×	

- 12. If corrections are needed, the Inspector shall sign each request for change and write down at the end of each form the number of changes requested.
- 13. Upon the completion of the Inspection, the Mini-grid Documentation and Inspection Forms, shall be signed by the NEMSA Inspector and countersigned by the Applicant.
- 14. A copy of the Mini-grid Documentation and Inspection Forms, as filled during the Inspection, shall be made available to the Applicant upon the completion of the Inspection.

3.4 Evaluation

- Upon the completion of the Inspection, NEMSA shall evaluate the compliance of the Minigrid with the existing Technical Standards and Technical Regulations for Mini-grids in Nigeria, as specified under Sections 2.3 and 2.4 of these Guidelines, based on the Minigrid Documentation and Inspection Forms, as filled during the Inspection and the Technical Documentation provided to the NEMSA Inspector during application for inspection exercise.
- 2. NEMSA shall communicate the outcome of the Evaluation, no later than two (2) weeks after the Inspection.

4 Inspection Certificate issuance

The Application, after the Evaluation, shall be categorized as:

- Certified: Where the Mini-grid is fully compliant with the technical standards and regulations, NEMSA shall issue an Inspection Certificate within one (1) week from the completion of the Evaluation, and the Applicant may start Servicing the Customers upon receipt of the Inspection Certificate;
- 2. Limited Safety Approval: Where minor non-compliance issues have been identified in the Mini-grid, NEMSA shall issue the Provisional Inspection Certificate within one (1) week from the completion of the Evaluation, upon which the Applicant may start Servicing the Customers, and shall have a period of 30 days to rectify the minor non-compliance issues communicated by NEMSA, upon such rectification and proof of the same submitted to NEMSA, an Inspection Certificate shall be issued by NEMSA within one (1) week; or
- 3. Rejected: Where major non-compliance issues have been identified in the Mini-grid, NEMSA shall not provide any (Provisional) Inspection Certificate and shall invite the Applicant to rectify all non-compliance issues identified during the Inspection and Evaluation for which the Mini-grid is not compliant and apply for a Re-Inspection, which shall follow the same process as Inspection set out above.

5 Sanction for non-compliance

After the period of 30 days, if the Applicant fails to communicate to NEMSA for the re-inspection towards certification, the Applicant's Provisional Approval will be revoked.


6 Dispute settlement

- Where an Applicant is aggrieved by the decision or Inspection carried out by NEMSA, He/she may file a written complaint to the Technical Committee of NEMSA within a period of fifteen (15) working days from such decision or Inspection by NEMSA, including all pertinent details, dates and documents, as applicable.
- The Technical Committee shall review and resolve the complaint and communicate the same to the Applicant within a period of fifteen (15) working days from the receipt of such complaint.
- 3. Where the Technical Committee fails to respond within fifteen (15) working days or the Applicant is aggrieved by the decision of the Technical Committee, the Applicant may forward the complaint to MD/CEO & CEIF for further necessary action.

7 Process Flow Diagram

The below process flow diagram presents the process as outlined above.

Figure 1: Flow Diagram for the process to obtain an inspection certificate



8 Annex - Mini-grid Documentation and Inspection Forms

- General Form A1
- General Form A2
- PV generator Layout and Single Line Diagram B1
- PV generator Specification of main components B2
- PV generator Test and verification B3
- PV generator Test and verification B4
- Battery storage Layout and SLD C1
- Battery storage Specification of main components C2
- Battery storage Test and verification C3
- Battery storage Test and verification C4
- Battery storage Test and verification C5
- System Controller Layout and SLD D1
- System Controller Specification of components D2
- Earthing and Surge Protection System E1
- Earthing and Surge Protection System E2
- General security F1

Mini-Grid Documentation and Inspection: General Form

w	n must be included in every applic	- words	TO be filled in	by the reprisent	A second		G	Н
1	Α	В	С	D D	E Authorized rep	F	Other	
		Mini-Grid Owner	Applicant (if di	fferent)	Authorized rep	Jiesemanve	Other	
1 0	Company name							
2	Street							
3 1	Further address details							A THE STATE OF THE
4	Town	NIEW NIEW						
5	Tax registration number						111	
6	Name of representative							
7	Position			W. Carlotte				
8	Telephone							
9	E-mail		Details of the	- Mini-Grid		- W		
		Federal state	District		Number of inl	nabitants	GPS Coordin	ates
<.	Name of the village	rederal state				WZ		
10				a facilities	Educational f	acilities	Health care f	acilities
	Main business activity #1	Main business activity #2	Administrativ	e racinues	Laucationari	<u> </u>		
11						· - PI 14/1-3	Storage man	ufacturer
	Total installed power [kVA]	Total solar PV installed [kW _p]	Storage techr	nology	Storage capa	city [kwn]	Storage man	ulactulei
12							Monitoring s	vetem
	System controller model	System controller manufacturer	Charge contr	oller manufacture	r Grid-tie inver	ter manufacturer	World of the S	ystem
13								line (AC/DC)
Other generation technology		Other manufacturer	Other model		Other rated p	ower [KVA]	Type of cour	oling (AC/DC)
14			1				4	
2.3	# Generator model	Manufacturer	Generator rat	ted power [kVA]	Operating	Year of constr.	Fuel type	Operation
15	1		Prime	Standby				
-	2		Prime	Standby		Vi		
10	4					1		

	Sito name	Date	Inspector name	Signature
NEMSA Reference number	Site name	Date		

Mini-Grid Documentation and Inspection: General Form This form must be included in every application and duly signed

NEMSA Reference number_____ Site name _____ Date ____

1	A B	To be filled	in by the Applicant	
ne	A B	C D	Е	F
17	Single Line Diagram			
18	Data of installation	Mini-Grid Owner	Full name of signatory	Signature
19	Date of application	Applicant (if different to Mini-Grid Owner)		
		To be fill	ed in by NEMSA	
	Responsible Inspectorate Field	Office Date of receipt of application	Processed by	Date
20				
21				
				r.

Inspector name_____ Signature

1	TOTAL STATE OF THE	chnical drawings – pages to be labelle To be filled in by the appli		To be filled in by NEMSA		
w A	ВС	D	F	H Com	ment	MDS
	ta de la constantina					
1						
						-
j j						
3 rel						4
Site layout						
_ io						
						į.
5						
3						
1.000						
7						
36						
Single Line Diagram						
8 2						
3						İ
] Bu						
9 35						
0						

NEMSA Reference number	Site name	Date	Inspector name	Signature
------------------------	-----------	------	----------------	-----------

Row A	В		С	D	o be filled in	by the app	licant F	G		To be filled in by NEMS.
7.					loque of solar	The state of the s		eets to be attached	THE HOLL	Comment
#	Manufacturer	Model		Technolog	y STC	ower [W _p]	Nb. of cells	MPPT Current	MPPT voltage	Verify data sheets attached
111 1										John y data directe ditabiled
112 2										
		-								
113 3										
			Cat	alogue of ch	narge controll	ers or grid-		d (data sheets to b	e attached)	
#	Manufacturer	Model		Technolog	y Rated	power	Rated voltage	Rated current		Verify data sheets attached
114 1		V								
115 2									wii caaa uu	
116 3										
	THE THE ATEL				Cata	aloque of s	tring combiner bo	oxes		
#	Model	SLD of	model #1			of model #2		SLD of model #3	3	Verify data sheets attached
117 1										#1
118 2										#2
119 3										#3
	Language of the second		curse we a	String refe	erences, num	ber of strin	as marked in the	SLD in lines 106	110	
Stri	ng number		1	2		3	4	5	6	Verify if installed correctly
120 Moc	lule catalogue #									
121 Nun	nber Series	S	P	S P	S	Р	S P	S P	S P	
State of the latest and the latest a							9	3 F	3 P	
122 Tota	al power [W _p]									
123 Fuse										
124 Surg	ge Protection									
Con from	verter catalogue #									
	lines 114 116									

Mini-Grid Documentation and Inspection: **PV generator – Test and verification**A little of the form by acquirelest test and verification reports according to IFC 62446 – pages to be labelled "B3". Use additional copies of this form if needed.

B3

pplica \	To be filled in by the applicant (p	referred)	or by NEMS	A inspector	(optional)				e filled in by NEMS	
Row	A	В	C	D	E	Facili	G	Comment		MDSF
		2		references			-	Verify Applied	nts' measurements	
-	String number	1	2	3	4	5	6	verily Applica	nts measurements	
127	Expected open circuit voltage [V]									
128	Measured open circuit voltage [V]									
129	Expected load circuit voltage [V]									
130	Measured load circuit voltage [V]									
131	Expected short circuit current [A]									
132	Measured short circuit current [A]									
133	Measured ambient temperature [°C]			(
134	Measured module temperature [°C]									
	Measured solar insulation [W/m²]									
136	Alternatively, estimated insulation (cloudy, sunny, mist,									
137	Expected power output [kW]									
138	Measured power output [kW]									
137	Measured insulation resistance [Mega Ohm]			W W-						
138	Measured continuity to main equipotential bar [Ohm]								21 82	
139	Measured earth resistance of support structure [Ohm]									
141	Result of verification of measured values (OK, low,)						The state of the s			

				And the control of th
NFMSA Reference number	Site name	Date	_ Inspector name	Signature

Row	To be filled in by the applicant (preferred)	or by NEMS	A inspector	(optional)	Delled D4		To be filled in by NEM	ISA
	A	В	С	D	E	F	G	Comment	MDISR
				references			Y. J. Carlo		
141	General visual inspection observations	- 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1	2	3	4	5	6	Verify applicant's visual inspect	ions
100	Surge Protective Devices functional (indicator at device)?		710-2						
	Overcurrent protection operational (correct fuse rating)?								
AND THE PERSON NAMED IN	String cables fixed and cables without damages								
145	Connectors properly connected under no mechanical strain								
146	1.33 MEAN TO THE STATE OF THE S		7001117						
147									
148									
149								- 11-101	
150									
151									
152	MANUFACTURE OF SALES AND								
153									
154									
155									
156	Summary of the visual inspections								
157	Date of the inspection								
158	Signature								
			*						

NEMSA Reference number	Site name	Date	Inspector name	Signature	
------------------------	-----------	------	----------------	-----------	--

210

Mini-Grid Documentation and Inspection: Battery storage – Layout and SLD

Applicant can replace this form by equivalent technical drawings – pages to be labelled "C1". Use building layout if more than one battery storage is installed to illustrate reference to the location the battery in the building. To be filled in by NEMSA To be filled in by the applicant MD SR Comment E 201 202 203 204 205 206 207 208 209

NEMSA Reference number	Site name	Date	Inspector name	Signature

Mini-Grid Documentation and Inspection: Battery storage – Specification of main components C2

Applicant can replace this form by equivalent technical description – pages to be labelled "C2" and to attach the data sheets of the storage system(s)

Manufacturer	Mode	С		D		E			100/2						A STATE OF THE PARTY OF THE PAR	- 10	
Manufacturer	Mada			A-4-1-				F		G	7,81	H	Comme	nt 💮		1	MD SF
Manufacturer	Bando									s to be atta							(Contraction)
	MOGE		Tech	nology	Cell v	oltage [V]	Batte	ry voltage	C10 C	apacity	Charge	voltage	Verify da	ita sheets	s attache	d	
	E.																
*														100000000000000000000000000000000000000			
-												-					-
	1 F		distance.	otalogua (s hattar	u atriaa aa	nfiaur	at an all and								1870 KENDEN NE THE	
Model	Batte	rv strina #1		ataiogue (Ratte	y sunig co rv strina #1	migura	auons and	Batto	monitorin rv string #3	g detans		Vorify	data e	hoote	ottoobod	0.0
Model	Dutte	ry string # i	ALCO AVISED		Datte	y saing ma	STEER TENNING		Datte	iy stillig #5			verily	uala s	Heels	allached	an
													#1				
													#2				
5									3				#3				
			Batter	string re	ference	s, number	of strii	ngs marked	in the	SLD in line	es 206 .	. 210					er un
ing number		1		2		3		4		5		6	Verify if	nstalled o	correctly		
dule catalogue #																	
mber Series	s	Р	S	Р	S	Р	s	Р	s	P	S	P					+
al C10 capacity								L									
VIII																	+
te of cell																	
duction or					4												
1 commissioning					į.												
ble cross-section																	
					i												
neral comments							,										
i c n	dule catalogue # mber Series allel al C10 capacity /h] e rating [A] e of cell duction or e of installation commissioning ole cross-section n²]	ing number dule catalogue # mber Series allel al C10 capacity /h ee rating [A] e of cell duction or e of installation commissioning ole cross-section 12]	ing number dule catalogue # mber Series S P allel al C10 capacity the rating [A] e of cell duction or e of installation commissioning ole cross-section 12]	Battery string #1 Battery Ba	Battery string #1 Battery string residue number 1 2 dule catalogue # mber Series S P S P allel al C10 capacity S P S P de rating [A]	Battery string #1 Battery string reference ing number dule catalogue # mber Series S P S P S allel al C10 capacity /h] be rating [A] e of cell duction or e of installation commissioning ole cross-section 12]	Battery string #1 Battery string references, number 1 2 3 dule catalogue # mber Series S P S	Battery string #1 Battery string references, number of string number 1 2 3 dule catalogue # mber Series S P S P S P S allel al C10 capacity //h the rating [A] e of cell duction or e of installation commissioning ole cross-section n²]	Battery string references, number of strings marked ing number 1 2 3 4 dule catalogue # Inber Series S P	Battery string #1 Battery string #2 Battery strin	Battery string #1 Battery string references, number of strings marked in the SLD in line ing number 1 2 3 4 5 dule catalogue # mber Series S P S P S P S P S P S P S P S P S P S	Battery string #1 Battery string #2 Battery string #3 Battery string #2 Battery string #3 Battery string #2 Battery string #3 Battery string #3 Battery string #2 Battery string #3 Battery string #2 Battery string #3 Battery string #3 Battery string #3 Battery string #3 Battery string #2 Battery string #3 Battery string #3 Battery string #2 Battery string #3 Battery string #2 Battery string #3 Battery string #2 Battery string #3 Battery string #2 Battery strin	Battery string references, number of strings marked in the SLD in lines 206 210 ing number 1 2 3 4 5 6 dule catalogue # nber Series	Battery string #1 Battery string #2 Battery string #3	Battery string #1 Battery string #2 Battery string #3 Verify data s #1 #2 #3 #3 #4 #4 #4 #4 #4	Battery string #1 Battery string #2 Battery string #3 Verify data sheets #1 #2 #3 Battery string references, number of strings marked in the SLD in lines 206 210 ing number	Battery string #1 Battery string #2 Battery string #3 Verify data sheets attached #1 #2 #3 Battery string references, number of strings marked in the SLD in lines 206 210 Ing number 1 2 3 4 5 6 Verify if installed correctly The catalogue # Index Series S P S

Mini-Grid Documentation and Inspection: Battery storage – Test and verification

Applicant can replace this form by equivalent test and verification reports according to IEC 62485 – pages to be labelled "C3" To be filled in by NEMSA To be filled in by the applicant (preferred) or by NEMSA inspector (optional) Row MD SR G Comment String references 6 Verify applicant's visual inspections 2 3 4 String number 1 228 General visual inspection observations 229 Wiring properly done without visual deficits Tightening torque of all screws to connectors to the batteries 230 and in between the cells of the batteries is according to the equipment manufacturer's recommendations Battery inverter or charge controller parameters are properly set (correct system configuration, date and time, control of the load shedding relays, reading of external temperature sensor verified. ...) 232 State of charge (If applicable state of health) 233 Safety measures for the respective types of batteries applied Deep discharge protection, over-charge protection and temperature monitoring installed and functional Number of full cycles calculated by the monitoring system (if applicable) 236 237 238 239 240 241

EMSA Reference number Site name	Date	Inspector name	Signature	
---------------------------------	------	----------------	-----------	--

	1.50			The Table		To be fill	ed in by ap	plicant						To be filled in by N	IEMSA
	↓ A	В	С	D	E E	F	G.	H		J	K		M	Comment	MDISR
									neters for b	attery st	ring #1				
	Cell number	1	2	3	4	5	6	7	8	9	10	11	12	Verify measurements	
	Cell voltage														
	Cell impedance	110													
244	Cell temperature														
	Cell number	13	14	15	16	17	18	19	20	21	22	23	24	Verify measurements	
	Cell voltage														
	Cell impedance														
247	Cell temperature											114-1			
	12 W								neters for b	attery st	ring #2	Transfer			
	Cell number	1.0	2	3	4	- 5	6	7	8	- 9	10	11	12	Verify measurements	
242	Cell voltage														
	Cell impedance										1				
244	Cell temperature	0-1111111111111111111111111111111111111													
	Cell number	13	14	15	16	17	18	19	20	21	22	23	24	Verify measurements	
245	Cell voltage														
246	Cell impedance Cell											-7113			
247	Cell temperature														

NEMSA Reference number	Site name	Date	Inspector name	Signature	
------------------------	-----------	------	----------------	-----------	--

Mini-Grid Documentation and Inspection: Battery storage – Test and verification

Applicant can replace this form by equivalent test and verification reports – pages to be labelled "C4", use additional sheets if more cells are installed

Applic	cant can replac	e mis iom	i by equiv	aieni iesi an	u veriiicaiii	To be fille	ed in by ap	plicant				t on the		To be filled in by N	
	A	В	С	D	E E	Face	G	Ha		J	- K		- M	Comment	MDSR
					Mea	asurement	of battery	cell param			ing #1				
	Cell number	1.1	2	3	4	- 5	6	7	- 8	9	10	11	12	Verify measurements	
248	Cell voltage														
249	mnanance														
225	Cell temperature														
	Cell number	13	14	15	16	17	18	19	20	21	22	23	24	Verify measurements	
Contract of the	Cell voltage									and Ar					
252	Cell														
253	Cell impedance Cell temperature				ALCOL										
Totallise	temperature		17-10-11-11		Me	asuremen	t of battery	cell paran	neters for	battery str	ing #2				
4	Cell number	1	2	3 .	4	5	6	7	8	9	10	11.	12	Verify measurements	
1502000000	Cell voltage														
255	Cell impedance								317-378						
256	Cell temperature														
	Cell number	13	14	15	16	17	18	19	20	21	22	23	24	Verify measurements	
257	Cell voltage														
258	Cell impedance							0							
259	Cell temperature														

NEMSA Reference number Site name	Date Insp	pector name Si	ignature
----------------------------------	-----------	----------------	----------

Mini-Grid Documentation and Inspection: System Controller – Layout and SLD

Applicant can replace this form by equivalent technical drawings – pages to be labelled "D1". Use building layout if more than one System Controller is installed to illustrate reference to the location in the building.

Rov	v			10-16		To b	e filled ir	by the a	pplicant				To be filled	in by NEMSA
	F	N. 11 3	В	selection of	C	D	4 = 1 = *	E A		F	G	H		MD
200														
301														
302	١.													
	∦ ફૅ													
303	1 6													
303) -													
304	α													
304		154												
305														
300														
		-					_	_						
306													77	
	W													
307														
307 308 309	ran													
	iad	AT .												
308	_ _ _													
	5													
	gle													
309	Sin													
503														
310														
4554	in an	4	1135											

NEMSA Reference number	Site name	Date	Inspector name	Signature	
------------------------	-----------	------	----------------	-----------	--

plica	rii Cc	ari repiace triis ioi	III by equivalent	To he	filled in by the ap	plicant		The Confidence	er(s) and charge controller(s) To be filled in by NEN	ISA
Row	Α	В	С	D	E	F	G	Har	Comment	MDS
	71	<u> </u>		Catalogue of it	nverters and char	ge controllers use	ed (data sheets to	be attached)	The second of th	
	#	Manufacturer	Model	Technology	Rated power	Rated voltage	Rated current	Features	Verify data sheets attached	
311	1									
312	2									
313	3			IV 32V						
314	4					No. 172-202-1				
315	5									
- 16	6	1			1	31				

NEMSA Reference number	Site name	Date	Inspector name	Signature
------------------------	-----------	------	----------------	-----------

To be filled in by the Applicant (preferred) or by NEMSA inspector (optional) To be filled in by NEMSA В C G Comment MD SR Reference to the inverter catalogue as per lines 311 ... 316 Device number 6 Verify applicant's visual inspections 317 General visual inspection observations 318 Inverter protection settings programmed to local requirements? When an RCD is installed to the AC circuit feeding an inverter, 319 the RCD type shall be verified to ensure it has been selected according to the requirements of IEC 60364 320 Means of isolating the inverter been provided on the AC side? 321 Isolating and switching devices been connected such that PC installation is wired to the "load" side and the public supply to 322 All Inverters/Charge controller operating correctly? 323 Inverter/charge controller protection settings and installer details displayed on site? 324 325 326 327 328 329 330

NEMSA Reference number Site nar	e Date	Inspector name	Signature
---------------------------------	--------	----------------	-----------

Mini-Grid Documentation and Inspection: Earthing and Surge Protection System

Applicant can replace this form by equivalent technical drawings – pages to be labelled "E1". Use site layout to illustrate the earthing arrangement and earth resistances measured and use the Single Line Diagram to clarify connections to the main earthing busbar, conductor cross sections, etc.

COO LING OIL	igie Eine Diagra	C C	To be filled	in by the Applica	nt			To be filled in I	NEMSA MD SR
KOW A	В	С	D	E	and Frederick	G	H	Comment	MD SR
401	\$-								
402									
and and									
403									
Site layout									
S)									
404									
701									
405									
403									


NEMSA Reference number	Site name	Date	Inspector name	Signature	
------------------------	-----------	------	----------------	-----------	--

Mini-Grid Documentation and Inspection: Earthing and Surge Protection System

Applicant can replace this form by equivalent technical drawings – pages to be labelled "E2". Use site layout to illustrate the earthing arrangement and earth resistances measured and use the Single Line Diagram to clarify connections to the main earthing busbar, conductor cross sections, etc.

To be filled in by the Applicant

To be filled in by NEMSA




NEMSA Reference number	Site name	Date	Inspector name_	Signature
	All		· · · · · · · · · · · · · · · · · · ·	

Mini-Grid Documentation and Inspection: General security

Applicant to add comments how the requirements are met or attach further documents for clarification. To be filled in by NEMSA To be filled in by the Applicant Row B Comment MD SR Fencing is installed to prevent access to the Generation Building structures are in good and stable condition Foundations are in good and stable condition Operating Procedures are displayed in public Smoke detectors are installed in the Power House 505 Firefighting equipment is available on site, is functional and local staff is trained to use it Warning signs indicating dangers and preventing access are installed Local staff is trained in emergency shut-down and general operating procedures Internal safety procedures are displayed and understood by local staff, provide last date of the safety training Internal procedures and measures for environmental protection are implemented and trained 511 512 513

NEMSA Reference number	Site name	Date	Inspector name	Signature
TALINO TICICI CITOC HATTIBET	Olto Harrio			





NIGERIAN ELECTRICITY MANAGEMENT SERVICES AGENCY